TECHNICAL SPECIFICATION



PressToCheck™ Compact P3 Filters with Odour Layer

Pack of 2 / BGC310-001-000



DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.97%, Low profile design maximising compatibility and low breathing resistance across the range.

F-3103 P3 dust compact filters with nuisance odour layer, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BGC310-001-000)

SAFETY STANDARDS

EN 143















SPECIFICATIONS

Classification

P3

Usage

R (Reusable)



Activated Carbon Layer

Maximum Total Inward Leakage (TIL) 2% when fitted to Force8 Half Mask

Nominal Protection Factor

48 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor

20 When fitted to Force8 Half Mask

Type

Press To Check Technology

Metal Free

Yes

Filter Shelf Life

5 Years



Overall Product Weight

52g



Filter Type

P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging

Yes - mandatory test in EN 143

Minimum Filtration Efficiency 99.95% For P3 Rated

Maximum Total Inward Leakage (TIL)

0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor

1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor

40 When Fitted To Force10 Full Face Mask

Latex free

Yes

Filter Material Polypropylene



BSI Kitemark

Yes

FEATURES





Compact Protection

Compact and lightweight ultra-low profile P3 protection, featuring PressToCheck™ technology.



Carbon Filter

Features an activated carbon filter layer, providing effective relief from nuisance odours (<WEL) for improved user comfort.'

VIDEOS

- youtu.be/1Y9G8E9kEXQ
- youtu.be/KOdO-cVil5A
- youtu.be/Ecyu_ftPPX4
- youtu.be/-oUSyP9_NsA

DOWNLOADS



Image Pack (ZIP)



doc-force-press-to-check-compact-filter-f-3103.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





