TECHNICAL SPECIFICATION



FilterSpec® & FilterSpec® Pro Replacement Filters

FFP3 Valved Filters - Pk10 / ASG03B-101-100



DESCRIPTION

Replacement filters compatible with FilterSpec® and FilterSpec® Pro.

FilterSpec® and FilterSpec® Pro Replacement Filters meet the requirements of EN 149 when fitted to FilterSpec® or FilterSpec® Pro product.

OPTIONS

FFP2 Valved Filters - Pk10 (ASG02B-101-100)

FFP3 Valved Filters - Pk10 (ASG03B-101-100)















SPECIFICATIONS

Classification

FFP3 (Filtering Facepiece Particulate)

Usage

NR (Non-reusable)

Minimum Filtration Efficiency 99% for FFP3 Rated

Nominal Protection Factor 50



Exhalation Valve



Product Weight 13g





Integration

FilterSpec's unique design overcomes the problem of ill fitting masks, fogged lenses and non-conformity that can often occur when one item of PPE compromises another.



Efficient Filter

The easily replaced filters are made from three layers for exceptional performance. Available with low resistance exhalation valve to reduce moisture and CO2 build-up.



Filter Type

P (Protects against solid and liquid aerosols)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

UK Assigned Protection Factor

Filter Shelf Life

5 years



Quality Lens

The FilterSpec® Pro goggle features a 5.5 base curve lens. FilterSpec® lenses have a base curve of 6.5. Both offer optimal coverage and feature anti-mist and anti-scratch lens coatings.





DOWNLOADS



Image Pack (ZIP)



doc-filterspec-ffp3-mask.pdf (PDF)







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





