

uvex

SAFETY
EYEWEAR

21.09.2015
SBU-E-PGM-PM

Product Datasheet model ultrasonic 9302 285



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* Panoramic lens shape allows 180° uninterrupted lateral vision* Medium-energy impact 'B' (120 m/s)* Integrated, indirect ventilation allows air movement directly across the lens* Fits comfortably over most prescription spectacles* Simple lens replacement* High-quality, easily adjustable headband
Technical details	
Frame	
Material	Front piece PP/TPE
Colour	black/grey
Material	Headband synthetic headband
Features	individually adjustable
Colour	grey/black

Manufacturer's ID code	Marking W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles) 9 (molten material and hot solids)
Low-energy impact	B (120 m/s)
Tested acc. to DIN	DIN
No. of certificat. body	0196
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,2 mm
Coating	supravision excellence
Colour	clear
Marking	
Filter	2-1,2 (DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	B (120 m/s)
Field of use	9 (molten material and hot solids)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
Miscellaneous	
Weight	80 g
Packing	4 goggles per box 72 pieces in one carton
Standards	DIN EN 166 + DIN EN 170