



PRODUCT NUMBER: 4503003  
**SPACEL 3000 AP / RA / EBJ**

Liquid tight coverall designed to protect workers from chemicals. Its new ergonomics offer a better fitting and protection. Model with elasticated wrists and ankles, double adhesive flap and back valve.

Overview

**Reference Number**

4503003

**Product Type**

Protective Clothing

**Range**

Disposable Clothing

**Brand**

Sperian

**Industry**

■ Chemical Industries ■ General Industry ■ Industrial Cleaning ■ Maintenance  
■ Offshore ■ Petro-chemical ■ Utilities

**Product Use**

Chemistry, petrochemistry, industrial maintenance, pharmaceutical industry, spoiled beach cleaning, transportation of hazardous materials, industrial sub-contracting cleaning, sanitation, waste processing, emergency services.

## Features & Benefits

### Feature

Enhanced protection

### Benefit

Double adhesive flap Welded zipper Very good abrasion, tear and puncture resistance Watertight due to "Spaseal" welding, an exclusive Honeywell Safety Product process Yellow for a better visibility

### Feature

Ergonomics

### Benefit

New design for better comfort and safety > Raw material elongation up to 400% Elasticated hood, waist, wrists and ankles Back ventilation valve

## Technical Description

### Description

Liquid tight overall designed to protect workers from chemicals. Its new ergonomics offer a better fitting and protection. Model with elasticated wrists and ankles, double adhesive flap and back valve.

### Gender

Unisex

### Size

From S to XXXL - International size

### Table Size

Table size

### Material

Polyethylene

### Color

Yellow

### Thickness

100µ

### Composition

Three-layered yellow polyethylene film

### Type of Protection

■ 4 ■ 6

### Performance


Type 4&6; Biological High chemical resistance Elongation up to 400% Double adhesive flap Back ventilation valve

### Limitation of use

This product is a single use garment. The user can wear this garment in association with other equipments (shoes, gloves, glasses, masks...). Do not use the overalls when there is a defect. When the closing system is faulty, the seams open or any other defects which appear.

### Warning

The choice and use of personal protective equipment must comply with the European Directive No. 89/656/CEE of 30/11/1989. The employer must have previously analyzed and assessed the risks linked to intervention and to those generated by the use of the personal protective equipment selected.




 **E.C. Declaration of Conformity**

**EC Category PPE**


3

**Quality Assurance**

ISO 9001 / 2000




We're sorry, there are no images available at this time.



Additional Information

**User Manual**

Spacel 3000 and 4000 User guide - indice f - 15 October 2012



Maintenance

**Life Cycle**


Disposable item. To be discarded after use. Do not reuse this item.

**Storage Information**

- 10° to + 40°C. In its original packaging and carton, optimal product use is ensured within three years of its manufacture.

**Care Instructions**

To be discarded after use.



Packaging

**Quantity per Carton**

25