

**Product Datasheet Safety Helmet pheos B  
with three variable ventilation zones**



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth**

<p><b>Product characteristics</b></p>	<ul style="list-style-type: none"> <li>* size and weight optimised helmet</li> <li>* trendy design</li> <li>* variable air vents at the front and the back of the helmet</li> <li>* optimal fit, high wearing comfort</li> <li>* 6-point textile suspension harness optionally with wheel ratchet system</li> <li>* approved and labeled for use in temperatures as low as <math>-30^{\circ}\text{C}</math></li> <li>* approved and labeled for Molten Metal</li> <li>* Adapter systems for uvex visors, uvex earmuffs and lamps with helmet attachment</li> <li>* suitable for head sizes of 51-61 cm resp. 52-61 cm (wheel ratchet system)</li> <li>* large printing areas</li> </ul>
---------------------------------------	---

<b>Technical details</b>	
<b>Helmet shell</b>	
Material	PE
Weight	ca. 296 g
<b>Interior</b>	<ul style="list-style-type: none"> <li>* 6-point-textile suspension harness</li> <li>* headband made of high quality PE</li> <li>* circulating pad</li> <li>* easy to replace sweatband</li> <li>* medically shaped neck band to prevent slide on overhead working</li> </ul>
<b>Versions</b>	<b>Conventional suspension harness</b>
Weight	ca. 86 g
Colours / Art. No.	white      9772 020 yellow     9772 120 orange     9772 220 red         9772 320 blue        9772 520 black       9772 920
	<b>Suspension harness with wheel ratchet system for infinite width adjustment</b>
Weight	ca. 98 g
Colours / Art. No.	white      9772 030 yellow     9772 130 orange     9772 230 blue        9772 530
<b>Packing</b>	25 pieces / box
<b>Standards</b>	DIN EN 397 in combination with EG-guideline 89/686/EWG with additional requirements for - “very low temperature” -30° C - “Molten Metal”