



TORA

Amber Hardium+ lens



FRAME

- Wraparound polycarbonate frame
- Integrated side and orbital protection
- Contoured temple set for improved fit
- Heat resistance : up to 90° C
- Extremely lightweight : 22 g



LENS

- Amber Polycarbonate 9D base curve for excellent field of vision and lateral coverage
- Optical quality class 1 (no distortion)
- Resistance to impact at extreme temperatures
- 100% UV filtration (in conformity with EN170)
- Hardium+ technology = superior anti-scratch and anti-fog coating
- Visible Light Transmittance = 87%

FIELDS OF USE

- Mechanical hazards (marking F - 45m/s) - solid particles projectiles (metal, wood... riveting, grinding, stone cutting, drilling..)
- UV radiation (accidental electric arc)
- Enhance contrast in low light conditions
- Surface inspection, wood lamp, shooting
- Protects against blue light
- Mist

DO NOT USE FOR

Does not protect against liquid, dust, molten metal, laser beam, or any kind of welding application

FRAME MARKING

CE 166 FT

CE = conformity marking

166 = n° of the standard

FT = impact resistance at extreme temperature (45m/s between -5° and +55°C)

EUROPEAN STANDARD

This product conforms to the European Council Directive 89/686/EEC and with the EN166 : 2001

EC-Type Examination Certificate n° 1343

Issued by INSPEC (notified body n°0194)
Upper Wingbury Courtyard, Wingrave, Aylesbury
Buckinghamshire, HP22LW, England

Conform to EN166 - EN170

LENS MARKING

2C-1,2 . AOS . 1 . FT

2C = UV filter with good color recognition (conform to EN170)

1,2 = shade number (yellow tint)

AOS = manufacturer Aearo

1 = optical class (permanent wear)

FT = impact resistance at extreme temperature (45m/s between -5° and +55°C)

PRODUCT REFERENCE

| Product Code | Frame | Lens | Material |
|---------------|-------|------|----------|
| 71501-00003CP | | | Hardium+ |

Supplied with a nylon cord