



TORA

Bronze Hardium+ lens



FRAME

- Wraparound polycarbonate frame
- Integrated side and orbital protector
- Contoured temple set for improved fit
- Heat resistance : up to 90° C
- Extremely lightweight : 22 g



LENS

- Bronze Polycarbonate 9D base curve solar lens for excellent field of vision and lateral coverage
- Optical quality class 1 (no distortion)
- Resistance to impact at extreme temperature
- 100% UV filtration (in conformity with EN170)
- Hardium+ technology = superior anti-scratch and anti-fog coating
- Visible Light Transmittance = 20%

FIELDS OF USE

- Outdoor mechanical tasks (marking F - 45m/s) - solid particles projectiles (metal, wood... riveting, grinding, stone cutting, drilling..)
- Construction
- UV radiation and sun glare (sunny conditions)
- Mist

DO NOT USE FOR

Does not protect against liquid, dust, molten metal, laser beam, or any kind of welding application

FRAME MARKING

CE 166 FT

CE = conformity marking

166 = n° of the standard

FT = impact resistance at extreme temperature (45m/s between -5° and +55°C)

EUROPEAN STANDARD

This product conforms to the European Council Directive 89/686/EEC and with the EN166 : 2001

EC-Type Examination Certificate n° 1343

Issued by INSPEC (notified body n°0194)
Upper Wingbury Courtyard, Wingrave, Aylesbury
Buckinghamshire, HP22LW, England

Conform to EN166 - EN172

LENS MARKING

5-2,5 . AOS . 1 . FT

5 = solar filter (in conformity with EN 172)

2,5 = shade number (brown-yellow tint)

AOS = manufacturer Aearo

1 = optical class (permanent wear)

FT = impact resistance at extreme temperature (45m/s between -5° and +55°C)

PRODUCT REFERENCE

Product Code	Frame	Lens	Material
71501-00002CP			PC Hardium+

Supplied with a nylon cord