

uvex

**SAFETY
EYEWEAR**

21.09.2015
SBU-E-PGM-PM

Product Datasheet model pheos 9192 225



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* Modern fashion-look* Duo spherical lens provides excellent all round vision* Eye plus-protection protects the eyebrows through an additional chamfer at the upper range* A slim temple geometry enables a comfortable wearing of earmuffs, helmets and caps* Outstanding ventilation ensures a well eye climate* Temple ends with non-slip components
Technical details Frame Material Features Colour	Front piece/Temple POM/TPE excellent ventilation black-green

Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,1 mm
Coating	supravison excellence
Colour	clear
Filter	
Manufacturer's ID code	Marking 2C-1,2 (DIN EN 170)
Optical class	W
Low-energy impact	1
Surface resistance to fine particles	F (45 m/s)
Antifog	K
Conformity symbol	N
	CE
Miscellaneous	
Weight	30 g
Packing	5 spectacles per box
	160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170