

**Product Datasheet model i-3 9190 880****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth****Product  
characteristics**

- \* Innovative protective spectacle, perfectly fit the face
- \* Individually adjustable side arms with variable inclination
- \* Integrated Softflex zone ensures outstanding wearer comfort for all head sizes
- \* Softflex nose piece ensures comfortable, pressure-free fit and remain firmly in place
- \* Soft ear and Softflex bridge pieces ensure a secure fit in any situation
- \* automatically darkening within 10 sec. and returning to original tint within 30 sec.
- \* glare protection
- \* new with proven uvex supravision HC-AF technology (anti-fog on the inside and extremely scratch resistant on the outside)

|  |   |
|--|---|
| <b>Technical details</b>                                       |   |
| <b>Frame</b>   |   |
| Material   | <b>Front piece/Temple</b><br>TPU/TPE          |
| Features   | variable inclination, individually adjustable |
| Colour   | black-anthracite                              |
|  | <b>Marking</b>                                |
| Manufacturer's ID code   | W   |
| Applicable EN norm   | 166   |
| Low-energy impact  | F (45 m/s)                                    |
| Resistance to high speed particles at extremes of temperatures | T   |
| Conformity symbol  | CE  |
| No. of certificat. body  | 0196  |
| <b>Lens</b>  |   |
| Material   | PC  |
| Thickness  | 2,2 mm  |
| Coating  | uvex supravision variomatic                   |
| Colour   | light green                                   |
|  | <b>Marking</b>                                |
| Filter   | 5-1,1<2 (DIN EN 172)                          |
| Manufacturer's ID code   | W   |
| Optical class  | 1   |
| Low-energy impact  | F (45 m/s)                                    |
| Surface resistance to fine particles                           | K   |
| Antifog  | N   |

**Miscellaneous**

Weight

30 g

Packing

1 spectacle per box

42 spectacles per cardboard box

Standards

DIN EN 166 + DIN EN 172