

Product Datasheet model super g 9172 086**UVEX ARBEITSSCHUTZ GMBH,
Würzburger Str. 181-189, D-90766 Fürth**

| | |
|--------------------------------|---|
| Product characteristics | <ul style="list-style-type: none">* Extreme lightweight – just 18 g* High-flexible frame made of high tech polymers* Wide field of vision* Metal-free frame* Great cover of eyebrow- and cheek area* Pleasant softly anti skidding temples thanks to x-stream-technology (XST)* Comfortable fit* Perfectly combinable with respirator mask |
| Technical details | |
| Frame | Front piece/Temple |
| Material | PA/TPE |
| Features | uvex XST-temple |
| Colour | titan |

| | |
|-------------------------|--|
| Manufacturer's ID code | Marking W |
| Applicable EN norm | 166 |
| Low-energy impact | F (45 m/s) |
| Tested acc. to DIN | DIN |
| Conformity symbol | CE |
| No. of certificat. body | 0196 |
| Lens | |
| Material | PC |
| Thickness | 1,5 mm |
| Coating | uvex supravision sapphire |
| Colour | grey |
| Filter | |
| Filter | Marking 5-2,5 (DIN EN 172) |
| Manufacturer's ID code | W |
| Optical class | 1 |
| Low-energy impact | F (45 m/s) |
| Tested acc. to DIN | DIN |
| Conformity symbol | CE |
| Miscellaneous | |
| Weight | 18 g |
| Packing | 5 spectacles per box 200 spectacles per cardboard box |
| Standards | DIN EN 166 + DIN EN 172 |