

Product Datasheet model super g 9172 281**UVEX ARBEITSSCHUTZ GMBH,
Würzburger Str. 181-189, D-90766 Fürth**

Product characteristics	<ul style="list-style-type: none">* Extreme lightweight – just 18 g* High-flexible frame made of high tech polymers* Wide field of vision* Metal-free frame* Great cover of eyebrow- and cheek area* Pleasant softly anti skidding temples thanks to x-stream-technology (XST)* Comfortable fit* Perfectly combinable with respirator mask
Technical details	
Frame	Front piece/Temple
Material	PA/TPE
Features	uvex XST-temple
Colour	anthracite/lime

Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificat. body	0196
Lens	
Material	PC
Thickness	1,5 mm
Coating	supravisión excellence
Colour	grey
Marking	
Filter	5-2,5 (DIN EN 172)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
Miscellaneous	
Weight	18 g
Packing	5 spectacles per box 200 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 172