

**Product Datasheet model skyguard NT 9175 261****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* An improved spectacle with all-round protection</li><li>* An injection moulded TPU frame increase wearer protection levels through minimising the risk of particle ingress</li><li>* The flexible, closed-pore soft components enables a customised, individual fit</li><li>* Easy to clean to promote long term use</li><li>* Comfortable, customized fit by individual side arm inclination and length adjustment</li></ul>
<b>Technical details</b>	
<b>Frame</b>	<b>Front piece</b>
Material	PP
Colour	blue
<b>TPU layer</b>	
Material	TPU
Colour	grey

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
<b>Material</b>	<b>Side piece</b> PBT+PC
<b>Features</b>	adjustable inclination
<b>Colour</b>	blue
<b>Material</b>	<b>Temple</b> PP
<b>Features</b>	adjustable to four different lengths
<b>Colour</b>	blue
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificate. body	0196
<b>Lens</b>	
<b>Material</b>	PC
<b>Thickness</b>	2,1 mm
<b>Coating</b>	supravision excellence
<b>Colour</b>	grey

	<b>Marking</b>
Filter	5-2,5 ( DIN EN 172)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	42 g
Packing	5 spectacles 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 172