

**Product Datasheet model skyguard NT 9175 275****UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

<b>Product characteristics</b>	<ul style="list-style-type: none"><li>* An improved spectacle with all-round protection</li><li>* An injection moulded TPU frame increase Wearer protection levels through minimising the risk of particle ingress</li><li>* The flexible, closed-pore soft components enables a customised, individual fit</li><li>* Easy to clean to promote long term use</li><li>* Individual side arm inclination</li></ul>
<b>Technical details</b>	
<b>Frame</b>	
Material	<b>Front piece</b> PP
Colour	grey
Material	<b>TPU layer</b> TPU
Colour	orange

Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Low-energy impact	F (45 m/s)
Conformity symbol	CE
Material	<b>Side piece</b> PBT+PC
Features	adjustable inclination
Colour	grey
Material	<b>Temple</b> PBT+PC
Colour	grey
Manufacturer's ID code	<b>Marking</b> W
Applicable EN norm	166
Low-energy impact	F (45m/s)
Tested acc. to DIN	DIN
Conformity symbol	CE
No. of certificate. body	0196
<b>Lens</b>	
Material	PC
Thickness	2,1 mm
Coating	supravision excellence
Colour	clear

	<b>Marking</b>
Filter	2-1,2 ( DIN EN 170)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Surface resistance to fine particles	K
Antifog	N
Tested acc. to DIN	DIN
Conformity symbol	CE
<b>Miscellaneous</b>	
Weight	43 g
Packing	5 spectacles 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170