

Product Datasheet model astrospec 2.0 9164 065



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Innovative style * Flexible 2K side arms and inclination * Secure and pressure-free fit * Wraparound side arms ensure perfect fit * Ventilation with labyrinth seal helps improve climate around the eyes * Panoramic polycarbonate lens with integrated side protectors for optimum coverage of the eyes * Folds flat
<p>Technical details</p> <p>Frame</p> <p>Material</p> <p>Colour</p> <p>Material</p> <p>Colour</p>	<p>Front piece</p> <p>PC+TPU</p> <p>blue</p> <p>Side piece</p> <p>POM</p> <p>grey</p>

Material	Temple
Colour	PC+TPU/TPE blue-light blue
Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,2 mm
Coating	uvex supravision sapphire
Colour	clear
Filter	Marking
Manufacturer's ID code	2C-1,2 (DIN EN 170)
Optical class	W
Low-energy impact	1
Resistance to high speed particles at extremes of temperat.	F (45 m/s) T
Surface resistance to fine particles	K
Conformity symbol	CE
Miscellaneous	
Weight	
Packing	37 g 5 spectacles per box
Standards	160 spectacles per cardboard box DIN EN 166 + DIN EN 170

