

### Product Datasheet model i-vo 9160 085



**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,  
D-90766 Fürth**

|                                                                                                                  |                                                                                                                                                                                                                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product characteristics</b>                                                                                   | <ul style="list-style-type: none"> <li>* Duo-spherical lens</li> <li>* Duo component technology</li> <li>* Extremely comfortable for all-day wear</li> <li>* Shock absorbing brow guard</li> <li>* Indirect ventilation</li> <li>* Quattroflex patented temple</li> <li>* Adjustable temple length and lens inclination</li> </ul> |
| <b>Technical details</b><br><br><b>Frame</b><br><br>Material<br>Colour<br><br><br>Material<br>Features<br>Colour | <b>Front piece</b><br>TPU/TPE<br>blue/grey<br><br><b>Side piece</b><br>PA<br>5 position length adjustability<br>blue                                                                                                                                                                                                               |

|                                                             |                           |
|-------------------------------------------------------------|---------------------------|
| Material                                                    | <b>Temple</b>             |
| Features                                                    | PBT+PC/TPE                |
| Colour                                                      | quattroflex temple        |
|                                                             | blue/grey                 |
|                                                             | <b>Marking</b>            |
| Manufacturer's ID code                                      | W                         |
| Applicable EN norm                                          | 166                       |
| Low-energy impact                                           | F (45 m/s)                |
| Resistance to high speed particles at extremes of temperat. | T                         |
| Conformity symbol                                           | CE                        |
| No. of certificat. body                                     | 0196                      |
| <b>Lens</b>                                                 |                           |
| Material                                                    | PC                        |
| Thickness                                                   | 3 mm                      |
| Coating                                                     | uvex supravision sapphire |
| Colour                                                      | clear                     |
|                                                             | <b>Marking</b>            |
| Filter                                                      | 2-1,2 ( DIN EN 170)       |
| Manufacturer's ID code                                      | W                         |
| Optical class                                               | 1                         |
| Low-energy impact                                           | F (45 m/s)                |
| Resistance to high speed particles at extremes of temperat. | T                         |
| Tested accord. to DIN                                       | DIN                       |
| Conformity symbol                                           | CE                        |

|                      |                                                          |
|----------------------|----------------------------------------------------------|
| <b>Miscellaneous</b> |                                                          |
| Weight               | 33 g                                                     |
| Packing              | 5 spectacles per box<br>200 spectacles per cardboard box |
| Standards            | DIN EN 166 + DIN EN 170                                  |