



OX2000

Clear DX lens



FRAME

- Wrap around polycarbonate frame
- Integrated side shields and orbital protection
- Specially designed to fit over prescription glasses
- Adjustable lock-in-temple (5 positions)
- Rotating tips (excellent grip in all positions)
- Non-slip rubber tips for additional comfort
- Weight : 35 g.



LENS

- Clear polycarbonate over-the-glass lens
- Optical quality class 1 (no distortion)
- Resistance to impact (45m/s)
- 100% UV filtration (in conformity with EN 170)
- DX coating : anti-fog, anti-scratch, anti-static and anti-chemical attack
- Visible Light Transmittance = 92%

FIELDS OF USE

- Over-spec use
- Mechanical hazards (marking F - 45m/s)
 - solid particles projectiles (metal, wood... riveting, grinding, stone cutting, drilling..)
- UV radiation (accidental electric arc)
- Mist

DO NOT USE FOR

Does not protect against liquid, dust, molten metal, laser beam, or any kind of welding application

FRAME & LENS MARKING

CE 2-1,2 . AOS . 1 . F EN166 - F

CE = conformity marking
 2 = UV filter (in conformity with EN 170)
 1,2 = shade number (Clear lens)
 AOS = manufacturer Aeero
 1 = optical class (permanent wear)
 F = low impact resistance (45m/s)
 EN166 = n° of the standard

EUROPEAN STANDARD

This product conforms to the European Council Directive 89/686/EEC and with the EN166 :1995

EC-Type Examination Certificate n°
 0070-683-085-05-01-0079

Issued by INRS (notified body n°0070)
 Avenue de Bourgogne - B.P. n°27
 54 501 Vandoeuvre Cedex, France

Conform to EN166 - EN170

PRODUCT REFERENCE

Product Code	Frame	Lens	Material
17-5118-2040P			PC DX