




PRODUCT NUMBER: 3301106

Laser Lite Single-Use (Corded)

[Learn more about our products at howardleight.com >](http://howardleight.com)

[Learn more about hearing conservation at hearforever.org >](http://hearforever.org)



Reference Number

3301106

Product Type

Hearing Protection

Range

Earplugs

Line

Disposable Earplugs

Brand


Howard Leight by Honeywell

Industry

- Industry ■ Administration ■ Agriculture ■ Army - Defence ■ ATEX environment
- Automotive and Part Manufacturer ■ Aviation ■ Building and Construction ■ Catering
- Chemical Industries ■ Energy or Electricity ■ Fire Protection brigades ■ Fishing
- Food Industries ■ Foundry ■ Glass Industries ■ Green Spaces ■ Homeland defense
- Industrial Cleaning ■ Iron and steel industry ■ Laboratory ■ Logistics ■ Maintenance
- Medical and Pharmaceutical ■ Metal steel ■ Mining and Quarrying ■ Offshore
- Paper Industries ■ Petro-chemical ■ Printing Industries ■ Services ■ Ship Building
- Telecoms ■ Textile Industries ■ Transportation ■ Utilities ■ Water treatment
- Welding ■ Wood Industries

Product Use

Single-Use Earplug




Feature

VIBRANT COLOURS Makes protection fun – and highly visible. SELF-ADJUSTING FOAM Polyurethane foam adjusts to fit virtually every wearer. CONTOURED T-SHAPE Aids in easy insertion, removal from ear canal.

Benefit

The bright idea in hearing protection, Laser Lite’s low-pressure foam expands gently inside the ear canal for comfortable long-term wear, while its contoured T-shape delivers easy handling. Its high visibility magenta and yellow colors make compliance checks quick and easy. Plus, Laser Lite is available with special packaging and dispenser options, ideal for process industries with low tolerances for packaging waste.



SNR (dB)

35

H (dB)

34

M (dB)

32

L (dB)

31

Attenuation Data

Frequency (Hz) Frequenz (Hz) Fréquence (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB) Mittlere Dämmung (dB) Atténuation moyenne (dB)	33.4	34.1	35.5	37.6	34.9	35.7	42.5	44.1
Standard Deviation (dB) Standardabweichung (dB) Déviation standard (dB)	4.6	4.7	4.6	4.1	5.0	2.8	2.9	4.2
Assumed Protection (dB) Angenommener (dB) Protection supposé (dB)	28.8	29.4	30.9	33.5	29.9	32.9	39.6	39.9

Size

Fits All

Color

Yellow and Magenta

Shape


t

Corded

Yes

Weight (grs)

0.48



Certifications

 E.C. Declaration of Conformity

EC Category PPE

2

Quality Assurance

ISO 9001 / 2000

EC Certificate Number


951095

EC Attestation

 EC Attestation

EC Attestation Number

9503632




We're sorry, there are no images available at this time.



Additional Information

User Manual

Instruction Manual - Laser Lite (global)



Maintenance

Life Cycle

These plugs must be disposed of and replaced after each wearing.

Storage Information

All earplugs should be stored before and between usages in a way that protects them from dirt, grease, and other contaminants.

Care Instructions

Disposable earplugs are made of either TPE (Thermoplastic elastomers) or polyurethane foam. Washing and cleaning of disposable earplugs are not recommended. These plugs must be disposed of and replaced after each wearing. Excessive moisture reduces the attenuation and slows down the foam recovery which may lead to improper fit.



Packaging

EAN Code

033552002215