

# TRIFTANE™ Tradition

## JALBIO J0271

**S2 HRO SRC**  
**EN 345-1**  
**35 to 47**



- **Aseptane™** upper
- **Triftane™** sole

- ❖ Loafer shoes ideal for food industry jobs
- ❖ White **Aseptane™** upper with microfiber resin combines optimal breathability and unmatched watertightness.
- ❖ Resistant to greasy and aggressive spilled and splashed liquids. Minimal stitching for improved hygiene and easy upkeep. Washable in soap and water
- ❖ Snug fit thanks to elastic band underneath protective tongue.
- ❖ Vamp lining in non-woven fabric. Resists scuffing and acid perspiration
- ❖ Stiffener reinforces the heel seat.
- ❖ Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration
- ❖ 200 Joules safety toecap is perforated for extra air flow around the toes.
- ❖ **TRIFTANE™** sole **technology** with a high adherence coefficient

- **Abrasion resistance : 81mm3.**

- NBR shore hardness : 60

- The protective NBR grid ensures the solidity of the whole to extend its useful life.

- **Heel shock absorbtion 28 Joule**

- Hollow heel, the hollowed out centre area makes wearers feel lighter as they walk.

- Softane™ comfort layer, density 0.45

**- All purpose :**

Resistant to oils and hydrocarbons, and acids and bases at low concentrations.

Resistant to direct contact heat up to

**300°C.**

- Antistatic

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC** (SRA+SRB)

**SRA** Test ground : ceramic/lubricant : water and detergent

On flat 0,49 (>0,32) – On the heel 0,54 (>0,28)

**SRB** Test ground steel/lubricant : glycerine

On flat 0,36 (>0,18) – On the heel: 0,24 (>0,13)

Weight	Gross weight (42): 1160 g / Net weight (42): 890 g												
Size	35	36	37	38	39	40	41	42	43	44	45	46	47
Packaging	5 pairs				10 pairs				5 pairs				
Dimensions	590x220x348				590x437x348				685x500x355			685x250x358	